

KNOW BEFORE YOU GO™



Solent Infrared Jammer Test Set

Part Number: EU00084-03-FG

Specifications subject to change without notice.

Providing confidence and reliability through total spectrum test and training solutions.

Solent is a confidence and laboratory test set used to verify infrared (IR) countermeasure systems such as the AN/ALQ-144, ALQ-157 and Matador in a completely unclassified manner. It is used to measure the modulation characteristics of IR countermeasure systems, as well as the radiant intensity of their jamming signals.

The Solent infrared jammer (IRJ) test set is a rugged, battery-operated system that can be handheld or supported on a simple tripod. The typical standoff range is 5-20 meters (m) or 15-65 feet (ft.) from the IR jammer. It can be used for confidence testing of fixed, swept and multi-tone jamming signals for both wide-beam and directional IR countermeasure systems.

Go/no-go testing can be performed for jammer radiant intensity, as well as integrity testing of jamming codes using the Solent's neural network. The measured results are displayed on a rear-mounted display in decibels (dB) of radiant intensity (above minimal measurable signal) and numerical identification of the jamming code.

The Solent IRJ test set can be supplied with an optional management software package for the training of the neural network using a "known good jammer." This occurs via a Recommended Standard, or RS, 232 serial port, where the "weighting" algorithms are stored on a removable memory media.

Specifications

Performance:	<ul style="list-style-type: none">Mid-IR band (single-band version) or Bands 1 and 4 (dual-band version); bands can be selected by use of external filtersBeam width 5 degrees (-3 dB)
Measurements:	<ul style="list-style-type: none">Minimum measurable signal 0.02 milliwatts per centimeter squared (mW/cm²)Maximum optical power greater than 5 mW/cm² before saturationMeasurement accuracy ±10 percentFrequency response 50 hertz to 3.2 kilohertz
Operating parameters:	<ul style="list-style-type: none">Typical operating range 5-20 m (15-65 ft.)Up to 10 test programsUp to 20 codes per jammerEight-second typical test duration
Power supply:	<ul style="list-style-type: none">Quantity of four AA cells (rechargeable nickel-metal hydride or standard alkaline)
Indicators:	<ul style="list-style-type: none">Sunlight-readable display
Controls:	<ul style="list-style-type: none">On/off switch and trigger on the hand gripButtons for test program selection and display brightness control
Connectors:	<ul style="list-style-type: none">External Bayonet Neill-Concelman, or BNC, connector for detector outputExternal power inputRemote communication connector
Dimensions:	<ul style="list-style-type: none">200 millimeters (mm) x 120 mm x 120 mm (0.7 ft. x 0.4 ft. x 0.4 ft.) excluding handleMass 2.6 kilograms (5.7 pounds) including batteries
Color:	<ul style="list-style-type: none">NATO green plus yellow removable strip
Environment:	<ul style="list-style-type: none">Operating temperature -20 to 55 degrees Celsius (°C) excluding batteriesStorage temperature -20 to 71°CCE markedSealed to International Protection Code 65Designed in accordance with MIL 28800 PRF and DEF STAN 66-31ATEX compliant to EN60079-15 for Zone 2, Category 3 equipment (Temperature Class T3)
Transport case:	<ul style="list-style-type: none">Containing ancillaries including the Solent unit, one spare battery pack, socket driver, battery charger and cable, and operation/maintenance manual

For information within the United States, please contact:

AAI Corporation
124 Industry Lane
Hunt Valley, MD 21030
800-655-2616
AAI_EO_IR@aai.textron.com

For information outside the United States, please contact:

ESL Defence Limited
16-17 Compass Point, Ensign Way
Hamble, Southampton Hampshire
SO31 4RA
+(44) 2380455110
sales@esldefence.co.uk